


110RH; 110RH-ST
Alloy Steel; Patent Design



DIMENSIONS

RATED CAPACITY	C1	C2	C3	H	H1	H2	L	W	W1	SUGGESTED SHACKLE
110RH:										
t/mm										
0.5; 1; 2	30.0	14.0	43.0	102.0	68.0	38.0	43.0	63.0	15.0	TBX-2t
3	32.0	18.0	55.0	119.0	80.0	39.0	55.0	83.0	18.0	TBX-3.25t
5	45.0	24.0	66.0	153.0	104.0	50.0	66.0	82.0	26.0	TBX-5t
10	60.0	33.0	73.0	195.0	125.0	50.0	73.0	90.5	40.0	TBX-12.5t
20	75.0	41.0	82.0	225.0	145.0	53.0	82.0	110.0	53.0	TBX-21t
30	87.0	44.0	92.0	248.0	150.0	50.0	92.0	125.0	58.0	Crosby G-2140-30t or TBX-30t
50	115.0	62.0	130.0	331.0	206.0	74.0	130.0	159.5	79.0	Crosby G-2140-55t or TBX-50t
100	170.0	88.0	-	442.0	260.0	65.0	176.0	213.0	122.0	Crosby G-2140-120t or TBX-110t
Ib/inches (conversion of above dimensions)										
1,102.3; 2,205.1; 4,409.2	1.18	0.55	1.69	4.02	2.68	1.50	1.69	2.48	0.59	TBX-2t
6,613.9	1.26	0.71	2.17	4.69	3.15	1.54	2.17	3.27	0.71	TBX-3.25t
11,023.1	1.77	0.94	2.60	6.02	4.09	1.97	2.60	3.23	1.02	TBX-5t
22,046.2	2.36	1.30	2.87	7.68	4.92	1.97	2.87	3.56	1.57	TBX-12.5t
44,092.5	2.95	1.61	3.23	8.86	5.71	2.09	3.23	4.33	2.09	TBX-21t
66,138.7	3.43	1.73	3.62	9.76	5.91	1.97	3.62	4.92	2.28	Crosby G-2140-30t or TBX-30t
110,231.1	4.53	2.44	5.12	13.03	8.11	2.91	5.12	6.28	3.11	Crosby G-2140-55t or TBX-50t
220,462.3	6.69	3.46	-	17.4	10.24	2.56	6.93	8.39	4.80	Crosby G-2140-120t or TBX-110t
110RH-ST:										
t/mm										
0.5; 1; 2	33.0	18.0	43.0	110.0	74.0	38.0	43.0	63.0	18.0	Crosby G-2130-2t or SBX-2t
3	35.0	21.0	55.0	129.0	88.0	39.0	55.0	83.0	25.0	Crosby G-2130-3.25t or SBX-3.25t
5	50.0	27.0	66.0	164.6	110.6	50.0	66.0	82.0	33.0	Crosby G-2130-6.5t or SBX-6.5t
10	63.0	37.0	73.0	205.0	135.0	50.0	73.0	90.5	41.0	Crosby G-2130-12t or SBX-12t
20	90.0	53.0	82.0	249.0	153.0	53.0	82.0	110.0	66.0	Crosby G-2130-25t or SBX-25t
Ib/inches (conversion of above dimensions)										
1,102.3; 2,205.1; 4,409.2	1.30	0.71	1.69	4.33	2.91	1.50	1.69	2.48	0.71	Crosby G-2130-2t or SBX-2t
6,613.9	1.38	0.83	2.17	5.08	3.46	1.54	2.17	3.27	0.98	Crosby G-2130-3.25t or SBX-3.25t
11,023.1	1.97	1.06	2.60	6.48	4.35	1.97	2.60	3.23	1.30	Crosby G-2130-6.5t or SBX-6.5t
22,046.2	2.48	1.46	2.87	8.07	5.31	1.97	2.87	3.56	1.61	Crosby G-2130-12t or SBX-12t
44,092.5	3.54	2.09	3.23	9.80	6.02	2.09	3.23	4.33	2.60	Crosby G-2130-25t or SBX-25t

110RH; 110RH-ST
Alloy Steel; Patent Design

SPECIFICATIONS			
Full Scale Output	2.0± 0.25% mV/V	Recommended Excitation	10V (15V Maximum)
Zero Balance	± 0.02 mV/V	Insulation Resistance	>2 [50V DC] GΩ
Non-linearity	<± 0.03%	Compensated Temperature Range	-10°C to 50°C / 14°F to 122°F
Repeatability	<± 0.03%	Safe Overload	200% of full scale
Hysteresis Error	<± 0.03%	Breaking Overload	500% of full scale
Creep in 30 min.	<± 0.03%	Seal Type / IP Rating	Environmentally Sealed / IP65
Input Resistance	400Ω ± 20 or 1100Ω ± 50	Cable Color Code	Exc+ Red Exc- Black
Output Resistance	350Ω ± 3 or 1000Ω ± 10		Sig+ Green Sig- White
Element Material	Alloy Steel, Powder Coating		Sen+ Blue Sen- Yellow
			Shield Bare

PART NUMBER			
110RH			
Rated Capacity	Output Resistance	Part No.	Self Weight with Cable (kg) Approx.
0.5t.....	350Ω	110RH-0.5t.....	0.8
	1000Ω	110RH-0.5t-T1.....	0.8
1t.....	350Ω	110RH-1t.....	0.8
	1000Ω	110RH-1t-T1.....	0.8
2t.....	350Ω	110RH-2t.....	0.8
	1000Ω	110RH-2t-T1.....	0.8
3t.....	350Ω	110RH-3t.....	1.2
	1000Ω	110RH-3t-T1.....	1.2
5t.....	350Ω	110RH-5t.....	1.7
	1000Ω	110RH-5t-T1.....	1.7
10t.....	350Ω	110RH-10t.....	2.4
	1000Ω	110RH-10t-T1.....	2.4
20t.....	350Ω	110RH-20t.....	3.8
	1000Ω	110RH-20t-T1.....	3.8
30t.....	350Ω	110RH-30t.....	6.2
	1000Ω	110RH-30t-T1.....	6.2
50t.....	350Ω	110RH-50t.....	13.3
	1000Ω	110RH-50t-T1.....	13.3
100t.....	350Ω	110RH-100t.....	32.7
	1000Ω	110RH-100t-T1.....	32.7

0.5t-3t: NTEP 1:3000 Class III, Single Cell;
NTEP 1:5000 Class III, Multiple Cell;
5t-50t: NTEP 1:3000, up to 1:6000 Class III, Single Cell and
Multiple Cell
1t-10t: OIML MAA C3, Y=15000
10t-50t: OIML MAA C3, up to C6, Y=13500