

## MCWN-RF

### MCWN-RF "NINJA" SERIES SUSPENDED CRANE SCALES WITH RADIO FREQUENCY MODULE



Professional and digital crane scales fitted with radio frequency module, for connection to PC, remote printer, or weight repeater. Thanks to their compact size, the MCWN crane scales just slightly reduce the lifting distance of the crane. Available also CE-M APPROVED. Fitted with test certificate obtained with sample weights

Working in cooperation with:

**Vetek AB**

Hantverksvägen 15 - 76040 - Väddö - SWEDEN  
Tel. 0046-176208920 Fax. 0046-176208929  
olle@vetek.se

The best solution  
for advanced industrial  
applications

## MAIN FEATURES

- Fitted with the following upper and lower shackle:
  - GR3 for MCWNT1
  - GR6 for MCWNT6
  - GR9 for MCWNT9.
- Compact size and minimum distance between upper and lower shackle.
- 25 mm LCD backlit display, easily visible in any lighting condition.
- Precision: +/- 0.03% on MAX.
- 5-key waterproof keypad: Zero, semi automatic or preset Tare, Mode, Print, On/Off.
- Sturdy case in oven-fire painted steel.
- Radio frequency module (868MHz) for connection to a PC or to a weight indicator/repeater.
- Optional Alibi memory for data transmission used in applications involving third parties relations.
- Fitted with infrared remote control for up to 8m distance use.
- Power supply through 4 AA batteries, which may be rechargeable.
- Auto switch-off.
- Energy saving function, in order to increase working autonomy.
- Digital calibration and programmable Set-Up directly from the keypad or from the PC with Dinitools.
- Adjustable digital filter according to the weighing conditions.
- Operating temperature: -10/+40 °C.
- RS232 serial port on the RJ11 connector for quick programming with Dinitools.
- Fitted with protective transport case with dimensions (WxLxH) 175x480x390mm.

## MAIN FUNCTIONS

- Identification of the weight peaks.
- Freezing of the weight on the display.
- Weighs accumulation.
- +/- check.
- Weigh percentile.
- Input/Output.
- X 10 high resolution visualisation.
- Net/Gross or lb/kg conversion.

## DETAIL 1



Protective transport case

## VERSIONS

### Versioni disponibili

Codice	Max (kg)	d (kg)	<b>M</b> (kg)
MCWNT1RF-4	300/600/1500	0,1/0,2/0,5	--
MCWNT1MRF-4 <b>M</b>	1500	--	0,5
MCWN11T6RF-3	1500/3000/6000	0,5/1/2	--
MCWN11T6MRF-3 <b>M</b>	6000	--	2
MCWNT9RF-3	3000/6000/9500	1/2/5	--
MCWNT9MRF-3 <b>M</b>	9000	--	5



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI AR GEO  
FRANCE sarl  
Nogent-sur-Marne

DINI AR GEO  
GMBH  
Sinsheim - Germany

DINI AR GEO  
UK Ltd  
Taunton - United Kingdom

DINI AR GEO WEIGHING  
INSTRUMENTS Ltd  
Shanghai - China

DINI AR GEO  
WEIGHBRIDGES  
Calto (RO) – Italy



HEAD OFFICE  
Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena - Italy



**Vetek AB**

Hantverk svägen 15 - 76040 - Väddö - SWEDEN

Tel. 0046-176208920 Fax. 0046-176208929

olle@vetek.se

SALES AND TECHNICAL ASSISTANCE SERVICE